YUQIANG LIGHTING PRODUCT CATALOG

All products

44 product models | Current published product data

LED Starlink Multifunctional Modules	21 models
LED Wall Washers	6 models
LED Linear Lights	3 models
LED Floodlights	4 models
LED Inground Lights	10 models

Images and specifications reflect the current product library. Missing images and documents are marked as pending. Final specifications must be confirmed for each project.

https://www.yqzmled.com

LED Starlink Multifunctional Modules / Starlink Wall Washers

X3 Starlink Wall Washer

YQ-XQ51W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	51W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Wall Washers

X2 Starlink Wall Washer

YQ-XQ34W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	34W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H55×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Wall Washers

X1 Starlink Wall Washer

YQ-XQ17W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	17W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H48×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T1 Starlink Floodlight

YQ-TG3W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T2 Starlink Floodlight

YQ-TG6W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	6W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W73×36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T4 Starlink Floodlight

YQ-TG12W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W73×73×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T6 Starlink Floodlight

YQ-TG18W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W108×72×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T9 Starlink Floodlight

YQ-TG27W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	27W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W108×108×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Floodlights

T12 Starlink Floodlight

YQ-TG36W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	36W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W145×108×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D1 Starlink Spike Light

YQ-CD3W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D2 Starlink Spike Light

YQ-CD6W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	6W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W73×36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D4 Starlink Spike Light

YQ-CD12W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W73×73×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D6 Starlink Spike Light

YQ-CD18W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W108×72×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D9 Starlink Spike Light

YQ-CD27W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	27W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W108×108×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Spike Lights

D12 Starlink Spike Light

YQ-CD36W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	36W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W145×108×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Column Lights

B1 Starlink Column Light

YQ-BZ1W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	1W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H48MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Column Lights

B2 Starlink Column Light

YQ-BZ2W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	2W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H55MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Column Lights

B3 Starlink Column Light

YQ-BZ3W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Tile Lights

B3 Starlink Tile Light

YQ-WL12W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×146×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Tile Lights

B2 Starlink Tile Light

YQ-WL6W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	6W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×73×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Starlink Multifunctional Modules / Starlink Tile Lights

W3 Starlink Tile Light

YQ-WL3W-24V-X01



Style reference image. Appearance varies by model.

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / JY Golden Ox

JY Golden Ox 18W Wall Washer

YQ-XQ18W-WW-24V-JY01

Product image pending

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H48×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / JY Golden Ox

JY Golden Ox 24W Wall Washer

YQ-XQ24W-WW-24V-JY01

Product image pending

View pending | View pending | View pending

Power	24W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H48×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / JY Golden Ox

JY Golden Ox 36W Wall Washer

YQ-XQ36W-WW-24V-JY01

Product image pending

View pending | View pending | View pending

Power	36W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H65×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / TY Iron Ox

TY Iron Ox 18W Wall Washer

YQ-XQ18W-WW-24V-TY01

Product image pending

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H28×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / TY Iron Ox

TY Iron Ox 24W Wall Washer

YQ-XQ24W-WW-24V-TY01

Product image pending

View pending | View pending | View pending

Power	24W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W36×H28×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Wall Washers / TY Iron Ox

TY Iron Ox 36W Wall Washer

YQ-XQ36W-WW-24V-TY01

Product image pending

View pending | View pending | View pending

Power	36W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W42×H28×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Linear Lights / LT Longteng

LT Longteng 12W Linear Light

YQ-XT12W-WW-24V-LT01

Product image pending

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W30×H48×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Linear Lights / JL Golden Dragon

JL Golden Dragon 12W Linear Light

YQ-XT12W-WW-24V-JL01

Product image pending

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W32×H48×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Linear Lights / YL Silver Dragon

YL Silver Dragon 12W Linear Light

YQ-XT12W-WW-24V-YL01

Product image pending

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	W21×H50×L1000MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Floodlights / JC Junchi

JC Junchi 9W Floodlight

YQ-TG9W-WW-24V-JC01

Product image pending

View pending | View pending | View pending

Power	9W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø140×H65MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Floodlights / JC Junchi

JC Junchi 18W Floodlight

YQ-TG18W-WW-24V-JC01

Product image pending

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø175×H70MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Floodlights / HG Huaguang

HG Huaguang 9W Floodlight

YQ-TG9W-WW-24V-HG01

Product image pending

View pending | View pending | View pending

Power	9W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø62×H85MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Floodlights / HG Huaguang

HG Huaguang 18W Floodlight

YQ-TG18W-WW-24V-HG01

Product image pending

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø108×H130MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GJ Guijia Inground Lights

GJ Guijia Inground Light 3W

YQ-DM3W-WW-24V-GJ01

Product image pending

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø100×H90MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GJ Guijia Inground Lights

GJ Guijia Inground Light 6W

YQ-DM6W-WW-24V-GJ01

Product image pending

View pending | View pending | View pending

Power	6W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø120×H90MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GJ Guijia Inground Lights

GJ Guijia Inground Light 12W

YQ-DM12W-WW-24V-GJ01

Product image pending

View pending | View pending | View pending

Power	12W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø160×H90MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / XW Xuanwu Inground Lights

XW Xuanwu Inground Light 1W

YQ-DM1W-WW-24V-XW01

Product image pending

View pending | View pending | View pending

Power	1W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø32×H81MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / XW Xuanwu Inground Lights

XW Xuanwu Inground Light 3W

YQ-DM3W-WW-24V-XW01

Product image pending

View pending | View pending | View pending

Power	3W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø42×H95MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / XW Xuanwu Inground Lights

XW Xuanwu Inground Light 6W

YQ-DM6W-WW-24V-XW01

Product image pending

View pending | View pending | View pending

Power	6W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø50×H95MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / XW Xuanwu Inground Lights

XW Xuanwu Inground Light 10W

YQ-DM10W-WW-24V-XW01

Product image pending

View pending | View pending | View pending

Power	10W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø80×H95MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GC Guicang Inground Lights

GC Guicang Inground Light 10W

YQ-DM10W-WW-24V-GC01

Product image pending

View pending | View pending | View pending

Power	10W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø80×H118MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GC Guicang Inground Lights

GC Guicang Inground Light 15W

YQ-DM15W-WW-24V-GC01

Product image pending

View pending | View pending | View pending

Power	15W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø100×H131MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.

LED Inground Lights / GC Guicang Inground Lights

GC Guicang Inground Light 18W

YQ-DM18W-WW-24V-GC01

Product image pending

View pending | View pending | View pending

Power	18W
Voltage	DC24V
Light color	1800~6000K / RGB / RGBW
Beam angle	15° / 20° / 30° / 10×45°
IP rating	IP65
Functions	Static single color / DMX512 / RDM
Dimensions	Ø120×H151MM
Materials	6063 aluminum + tempered glass
Features	Compact size, efficient heat dissipation and double waterproofing

Dimension drawing - Pending | IES / Photometric data - Pending | Technical briefing - Pending

Scan to view the online product page. Online links require the updated website to be published.